

## How to change your TWCO bracelet and silicon strap.



In this instruction manual you will see how easy it is to change your TWCO bracelet, for instance for the TWCO silicon strap.

In picture 1 you see the spring bar tool, this tool is required for the actions we are showing.

Make sure your TWCO lies on a soft cloth (face down).

1. Take the spring bar tool and put the fork in the shoulder of the spring bar (see picture 2).
2. Press the spring bar inwards with the spring bar tool. Now you have one side loose, do the same thing on the other side of the spring bar.
3. If you done it correctly it should look like picture 3. Make sure you use your finger and thumb while you pull off the bracelet of the case, with this method your spring bar will not jump out.
4. Repeat this for the other side of the bracelet.

You will also notice that the watch case has double lug holes. Check out [www.twcowatches.com](http://www.twcowatches.com) for an explanation.

Now you can put on the TWCO silicon strap! Follow the procedure below! Make sure your TWCO lies on a soft cloth (face down).

1. First put on the piece that has the buckle.
2. Place the spring bar in the hole of the silicon strap.
3. Place the silicon strap onto the watch case as seen in picture 4, this should be put on the side of 12 o'clock (so at the 'top' side of the watch).
4. Press the spring bar, after you made sure the other side is already in the lug hole, and put it in the opposite lug hole.
5. For the other part of the silicon strap (the part without the buckle) just repeat the same procedure.

**Make sure both sides of the spring bar are correctly placed in the lug holes! Always test this before you put on your TWCO!**

